

EU Declaration of Conformity

<i>Product:</i>	Global Moulded Case Circuit Breakers	
-----------------	---	--

<i>Name and address of the manufacturer:</i>	<i>Name and address of the authorised representative:</i>	
Rockwell Automation, Inc.	Rockwell Automation B.V.	
1201 South 2nd Street	Rivium Promenade 160	
Milwaukee, WI 53204	2909 LM Capelle aan den IJssel	
USA	The Netherlands	

This declaration of conformity is issued under the sole responsibility of the manufacturer.

<i>Object of the declaration:</i>	Allen-Bradley 140G-M Series	
	<i>(reference the attached list of catalogue numbers)</i>	


The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:

2014/35/EU	Low Voltage Directive	(LVD)
2014/30/EU	EMC Directive	(EMC)
2011/65/EU	RoHS Directive	(RoHS)

References to the relevant harmonised standards used or references to the other technical specifications in relation to which conformity is declared:

EN 60947-2:2006 + A1:2009 + A2:2013	Low-voltage switchgear and controlgear – Part 2: Circuit-breakers
EN 50581:2012	Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances

Signed for and on behalf of the above named manufacturer:

<i>Place and date of issue:</i>	Milwaukee, WI USA	08-Sep-2017
<i>Name, function:</i>	Daniel L. Nachtigall – Technical Leader, Product Compliance Engineering	
<i>Signature:</i>		

<i>Catalogue number</i>	<i>Series ¹</i>	<i>Description</i>
140G-MxXx		800 A circuit breaker frame per Nomenclature
140G-MTxx-x		800 A circuit breaker trip unit per Nomenclature
140G-Mxxx-x-x-x		800 A circuit breaker assembly per Nomenclature

1) If no series number is given, then all series are covered.

NOMENCLATURE

Circuit Breaker Frame:

140G	-	M	6	X	3
I		II	III	IV	V

I	Product Type 140G – Global moulded case circuit breaker
II	Frame/Current Rating M – M frame/800 A
III	Interrupting Rating/Breaking Capacity (Based on I _c at 480V) 5 – 50 kA 6 – 65 kA 0 – 100 kA
IV	Protection Type X – None, frame only
V	Number of Poles 3 – 3 poles 4 – 4 poles

Circuit Breaker Trip Unit:

140G	-	M	T	I	4	-	D60
I		II	III	IV	V		VI

I	Product Type 140G – Global moulded case circuit breaker
II	Frame/Current Rating M – M frame/800 A
III	Interrupting Rating/Breaking Capacity (Based on I _c at 480V) T – None, trip unit only
IV	Protection Type F – Adjustable thermal/adjustable magnetic H – Electronic LSI I – Electronic LSIG K – Electronic LSIG-MM (maintenance mode)
V	Number of Poles 3 – 3 poles 4 – 4 poles
VI	Current Rating (* Denotes a two digit number) D* – Current ratings of 600...800 A

NOMENCLATURE

Complete Circuit Breaker Assemblies:

140G	-	M	6	I	4	-	D60	-	SB	-	AA
I		II	III	IV	V		VI		VII		VIII

I	Product Type 140G – Global moulded case circuit breaker
II	Frame/Current Rating M – M frame/800 A
III	Interrupting Rating/Breaking Capacity (Based on I _c at 480V) 5 – 50 kA 6 – 65 kA 0 – 100 kA
IV	Protection Type F – Adjustable thermal/adjustable magnetic H – Electronic LSI I – Electronic LSIG K – Electronic LSIG-MM (maintenance mode)
V	Number of Poles 3 – 3 poles 4 – 4 poles
VI	Current Rating (* Denotes a two digit number) D* – Current ratings of 600...800 A
VII	Factory-Installed Internal Options Blank – No installed option SJ – Shunt trip; 24...30V AC/DC SK – Shunt trip; 48...60V AC/DC SD – Shunt trip; 110...127V AC, 110...125V DC SA – Shunt trip; 220...240V AC, 220...250V DC SB – Shunt trip; 380...440V AC SC – Shunt trip; 480...525V AC UJ – Undervoltage release; 24...30V AC/DC UR – Undervoltage release; 48V AC/DC UY – Undervoltage release; 60 V AC/DC UD – Undervoltage release; 110...127V AC, 110...125V DC UA – Undervoltage release; 220...240V AC, 220...250V DC UB – Undervoltage release; 380...440V AC UC – Undervoltage release; 480...525V AC
VIII	Factory-Installed Internal Options Blank – No installed option AA – 1 auxiliary contact; 1 alarm contact, 250V CA – 3 auxiliary contacts; 1 alarm contact, 250V FB – 2 auxiliary contacts; 400V AB – 1 auxiliary contact, 1 alarm contact; 400V CJ – 3 auxiliary contacts, 1 alarm contact; 24V