


EU Declaration of Conformity

Product:	Trapped Key Safety Interlock Switches	
Name and address of the manufacturer: Rockwell Automation, Inc. 1201 South 2nd Street Milwaukee, WI 53204 U.S.A.	Name and address of the authorised representative: Rockwell Automation B.V. Rivium Promenade 160 2909 LM Capelle aan den IJssel The Netherlands	
<i>This declaration of conformity is issued under the sole responsibility of the manufacturer.</i>		
Object of the declaration:	Allen-Bradley / Guardmaster 440T Series (reference the attached list of catalogue numbers)	
<i>The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:</i>		
2006/42/EC	Machinery Directive	(MD)
2011/65/EU	RoHS Directive	(RoHS)
<i>References to the relevant harmonised standards used or references to the other technical specifications in relation to which conformity is declared:</i>		
EN ISO 13849-1:2008	Safety of machinery – Safety related parts of control systems – Part 1: General principles for design	
EN ISO 13849-2:2012	Safety of Machinery – Safety related parts of control systems – Part 2: Validation	
EN 60204-1:2006 + A1:2009	Safety of machinery – Electrical equipment of machines – General requirements	
EN ISO 14119:2013	Safety of machinery – Interlocking devices associated with guards – Principles for design and selection	
EN 50581: 2012	Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances	
Notified Body: performed: and issued the certificate(s):	TÜV Rheinland Industrie Service GmbH, Koln, Germany (NB 0035) EC Type Examination 01/205/5370.01/15	
Person authorised to compile the technical file (MD):	Authorised representative (see details above).	
Product Safety Function (MD):	Type 1 interlocking devices per EN ISO 14119 and Pl d, Cat 3 per EN ISO 13849-1.	
<i>Signed for and on behalf of the above named manufacturer</i>		
Place and date of issue:	Milwaukee, WI USA	02-January-2019
Name, function:	Daniel L. Nachtigall, Technical Leader – Product Certification Engineering	
Signature:		

<i>Catalogue number ¹</i>	<i>Series ²</i>	<i>Description</i>
440T-MRKS***# 440T-MRPS***#		Enclosure mount rotary switch, 4 N.O., 3 N.O. + 1 N.C., 3 N.O. + neutral, 3 N.O., 3 N.C., or 2 N.O. + 2 N.C. contacts, 20...100A/pole
440T-MMRS***#% 440T-MMRX***#%		Panel mount rotary switch w/key isolator, 4 N.O. or 2 N.O. + 2 N.C. contacts, 20...63A/pole
440T-MSRU***#		Panel mounted solenoid release unit, 4 N.O., 3 N.O. + 3 N.C., or 2 N.O. + 2 N.C. contacts, 20...63A/pole
440T-MS2097*# 440T-MS3417*# 440T-MS3418*#		Panel mount solenoid release unit, 4 N.O., 3 N.O. + 3 N.C., or 2 N.O. + 2 N.C. contacts, 20...63A/pole
440T-MKEX***#%		Mechanical key exchange unit
440T-MSBL***#% 440T-MDBL***#% 440T-MTBL***#% 440T-MQBL***#%		Mechanical bolt interlock
440T-MSBS***#% 440T-MDBS***#%		Electrical bolt interlock, 2 N.C. + 1 N.O. contact
440T-MSBU***#% 440T-MDBU***#%		Solenoid bolt interlock, 2 N.C. + 1 N.O. contact
440T-MSAL***#% 440T-MSCL***#% 440T-MDAL***#% 440T-MDCL***#% 440T-MQCL***#% 440T-MQAL***#% 440T-MTAL***#% 440T-MTCL***#% 440T-MPAL***#%		Mechanical lever/chain access interlock
440T-MDAS***#% 440T-MDCS***#%		Electrical lever/chain access interlock, 2 N.C. + 1 N.O. contact
440T-MDAU***#%		Mechanical lever/chain access interlock with solenoid contacts
440T-MSSL***#% 440T-MDSL***#%		Slamlock mechanical tongue-actuated interlock
440T-MSSS***#% 440T-MDSS***#%		Slamlock electrical tongue-actuated interlock, 2 N.C. + 1 N.O. or 2 N.C. + 2 N.O. contacts
440T-MSSU***#% 440T-MDSU***#%		Slamlock solenoid tongue-actuated interlock, 2 N.C. + 1 N.O. contact
440T-VMVL***# 440T-VPVL***#		Valve interlock
440T-MSGAU***#		Switchgear adapter
440T-MS@		Custom Interlock (Individual components)
440T-MSYS@		Custom interlock System (multiple components)

1) * Denotes a number or letter defining specific characteristics related to contact configuration/type, current, voltage, actuator type, and/or key interlock/configuration types.

Denotes Primary Key Code (may be multiple primary key codes)

% Denotes Secondary Key Code (may be multiple secondary key codes)

@ Denotes custom configuration codes (i.e. 1158, 3118, 3246, 3426, 3450, 3465, 3470)

2) If no series number is given, then all series are covered.