

EU Declaration of Conformity

Product: Global Moulded Case Switch Disconnectors

Name and address of the manufacturer: Name and address of the authorised representative:

Rockwell Automation, Inc.

Rockwell Automation B.V.

1201 South 2nd Street

Rivium Promenade 160

Milwaukee, WI 53204 2909 LM Capelle aan den Ijssel

USA The Netherlands

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration: Allen-Bradley 140G Series

(reference the attached list of catalogue numbers)

The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:

2014/35/EULow Voltage Directive(LVD)2014/30/EUEMC Directive(EMC)2011/65/EURoHS Directive(RoHS)

References to the relevant harmonised standards used or references to the other technical specifications in relation to

which conformity is declared:

EN 60947-3:2009 + A1:2012 + Low-voltage switchgear and controlgear – Part 3: Switches, disconnectors,

A2:2015 switch-disconnectors, and fuse-combination units

EN 50581:2012 Technical documentation for the assessment of electrical and electronic

products with respect to the restriction of hazardous substances

Signed for and on behalf of the above named manufacturer:

Place and date of issue: Milwaukee, WI USA 02-Apr-2019

Name, function: Daniel L. Nachtigall – Technical Leader, Product Compliance Engineering

Daint L. Hachtigall

Signature:



Catalogue number	Series 1	Description
140G-G6S3-D12		125 A isolation disconnector, 1250 A magnetic trip, 3 pole
140G-G6S4-D12		125 A isolation disconnector, 1250 A magnetic trip, 4 pole
140G-H6S3-D12		125 A isolation disconnector, 1250 A magnetic trip, 3 pole
140G-H6S4-D12		125 A isolation disconnector, 1250 A magnetic trip, 4 pole
140G-I3S3-D22		225 A isolation disconnector, 2250 A magnetic trip, 3 pole
140G-I3S4-D22		225 A isolation disconnector, 2250 A magnetic trip, 4 pole
140G-J0S3-D25		225 A isolation disconnector, 2500 A magnetic trip, 3 pole
140G-J0S4-D25		225 A isolation disconnector, 2500 A magnetic trip, 4 pole
140G-K15S3-D40		400 A isolation disconnector, 5000 A magnetic trip, 3 pole
140G-K15S4-D40		400 A isolation disconnector, 5000 A magnetic trip, 4 pole
140G-M6S3-D80		800 A isolation disconnector, 10,000 A magnetic trip, 3 pole
140G-M6S4-D80		800 A isolation disconnector, 10,000 A magnetic trip, 4 pole
140G-N6S3-E12		1200 A isolation disconnector, 20,000 A magnetic trip, 3 pole
140G-N6S4-E12		1200 A isolation disconnector, 20,000 A magnetic trip, 4 pole
140G-R12S3-E25		2500 A isolation disconnector, 25,000 A magnetic trip, 3 pole
140G-R12S4-E25		2500 A isolation disconnector, 25,000 A magnetic trip, 4 pole

¹⁾ If no series number is given, then all series are covered.